

DHL32

32" FHD LCD Monitor



Features:

- Industrial level LCD panel, suitable for extensive 24/7 continuous works
- High fidelity digital processing, brilliant and vivid video
- Low response time, no picture ghosting
- Built-in 3D COMB filter and 3D Noise Reduction
- Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
- Infrared, RS232 double mode, supporting remote PC control
- Professional thermal design to extend equipment lifespan
- Using tamper-proof metal housing, stable and reliable

Technical Specification

Model

Model	DHL32
-------	-------

System

Diagonal	31.5"(16:9)
Resolution	1920×1080
Backlight	LED
Brightness/Luminance (Standard)	350 cd/ m ²
Contrast	1200:1
Angle of View	178°/178°(vertical/horizontal)
Response Time	8ms
Display Color	8bit(16.7M)
VESA	300×300mm

Signals

Input	CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, Audio×1, RJ45×1, USB×1	
Output	CVBS(BNC)×2, RJ45×1	
	Speaker	2W×2

General

Consumption (Standard)	35W
Consumption (Standby)	≤1W



Power Supply	AC100~240V (+/-10%), 50/60 Hz
Net Weight	10kg
Gross Weight	14kg
Dimensions(no base)	750.7×455.1×44.0(mm)
Work Environment	Temperature: 0 C~50 C
	Humidity: 20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

Dimensions(mm)

